

Keyboard with Cardreader

rugged

IP54

Keyboard



Technical Specification Keyboard

- 89-eyes (emulates 101/102 Key-Keyboard for Windows)
- PS/2 compatible trackpoint and mousebutton
- Backlight for working in dark environment or at night (can be switched on and off)
- Lift of key: 2 mm
- Lifetime > 1 million actuations

Technical Specification Cardreader

- Class 2 Cardreader with display
- Display with 2 x 16 rows (lighting can be switched on- and off)
- Pin Pad with 16 keys
- Smart Card interfaces:
Supports T=1, T=0, I²C, SLE4432/42 (S=10), SLE4418/28 (S=9)
- Automatic detection of Smart Card types
- Supports Smart Cards with 5 V, 3 V and 1,8 V power supply
- Transfer rate from reader to card with 420 KBits per second
- Short circuit - and overheating protected
- Compliance / certification: Microsoft WHQL, EMV2000, ISO 17816, HBCI, USB 2.0, Common Criteria EAL 3+, PKI compliant
- API: PC/SC, CT-API, CCF
- PC/SC driver support: Windows®98, Windows®ME, Windows®2000, Windows®XP, Linux®

Certification / Environmental

- Water- and dust protected / IP54
- MIL STD 810F
- MIL STD 461E (optional)
- COMSEC Zone 1 / SDIP 27 Class A (optional)
- CE conform

Technical Data

- Dimension: 398 mm x 174 mm x 32 mm
- Power input: <2 W
- Weight: 1.5 kg

v1.0



Landstraße 6
77839 Lichtenau, Germany
www.roda-computer.com

Tel.: +49 (0) 72 27 / 95 79 - 0
Fax: +49 (0) 72 27 / 95 79 - 20
mail@roda-computer.com

roda computer GmbH reserves the right to update the information at any time without notice

roda
solid IT-solutions