

# AC/DC-Adapter

IP65

AC90  
power supply



 **WATER**  **SAND**

 **FROST**  **HEAT**

 **SHOCK**  **DROP**

## Technical Specification

|                            |                                                                                                                                                                           |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Input Voltage</b>       | 100 - 240 V <sub>AC</sub>                                                                                                                                                 |
| <b>Frequency</b>           | 50 - 400 Hz                                                                                                                                                               |
| <b>Input Current</b>       | 1.2 A                                                                                                                                                                     |
| <b>Output Voltage</b>      | 19 V <sub>DC</sub>                                                                                                                                                        |
| <b>Output Current</b>      | 4.74 A                                                                                                                                                                    |
| <b>Total Power</b>         | 90 W                                                                                                                                                                      |
| <b>Connector Type (DC)</b> | 3-pol. MIL, fixed cable ca. 0.97 m, (Amphenol 62IN-56T8-33S-622-RH)                                                                                                       |
| <b>Connector Type (AC)</b> | EU, UK, US as standard, fixed cable ca. 1.5 m<br>• others or open end on request                                                                                          |
| <b>Compatibility</b>       | suitable for all roda products with 3 pol. MIL DC connector:<br>• Rocky® RT8/RK8/RF8, RT9/RK9/RF9, RK10/RF10, RK12<br>• Panther DR8/DK8, DR10/DK10<br>• Lizard® RS11/RV11 |
| <b>Ingress Protection</b>  | IP65                                                                                                                                                                      |
| <b>Temperature</b>         | -30°C to +55°C (operating) / -30°C to +80°C (storage)                                                                                                                     |
| <b>Dimensions</b>          | ca. 300 x 113 x 65 x mm (L x W x H) without cable                                                                                                                         |
| <b>Weight</b>              | ca. 1.945 kg                                                                                                                                                              |
| <b>Option</b>              | • Explosive Atmosphere according to MIL-STD-810G, Method 511<br>• MIL-STD 461F Ground Army<br>• TEMPEST Zone 1 / SDIP 27 Level B (ER)                                     |

| Part no. | Description                                     |
|----------|-------------------------------------------------|
| 759038   | Rx/Dx AC-Adapter 90W, MIL - IP65                |
| 759039   | Rx/Dx AC-Adapter 90W, MIL, G.A. - IP65          |
| 759040   | Rx/Dx AC-Adapter 90W, MIL (G.A.), Zone 1 - IP65 |



Landstraße 6  
77839 Lichtenau, Germany  
www.roda-computer.com

Tel.: +49 (0) 72 27 / 95 79 - 0  
Fax: +49 (0) 72 27 / 95 79 - 20  
mail@roda-computer.com

roda computer GmbH reserves the right to update the information at any time without notice

**roda**  
solid IT-solutions